

Multiband 5-in-1 Sharkfin Antenna

2x 617-6000MHz, 2x 2.4/5GHz, 1x GNSS, 1x Whip/Terminal Ant



- ❖ Sharkfin 5-in-1 Omni Antenna with additional pass-thru port for Whip or Terminal antenna
- ❖ 2x2 Ultra-wideband (617-6000MHz) to support MIMO/diversity at 4G/5G, 2x MIMO Wi-Fi 2.4/5GHz, GNSS/GPS antenna w/ 26dB gain LNA, and external whip supports most frequencies
- ❖ Indoor and Outdoor rated IP69K design with UV stabilized radome
- ❖ Compatible with wide array of mobile and industrial gateways

Connector Option	Product SKU	Ventev Part #
SMA/RP-SMA	254950	VM-UWG2211OS-SM

Electrical Specifications		
Cable Leads Number	Cable 1 to 2 (4G/5G Elements)	Cables 3 to 4 (Wi-Fi Elements)
Frequency Bands, MHz	617-960/1960-6000	
Gain, dBi	617-960 MHz	4 dBi
	1690-2700 MHz	6 dBi
	3300-4200 MHz	7 dBi
	4900-6000 MHz	8 dBi
Polarization	Vertical	
Azimuth (HBW)	Omni (360°)	
Isolation, dBm	> 10	> 18
VSWR	≤ 2.0	≤ 2.0
Max Input Power per Port (W)	25	
Impedance, ohm	50	
GNSS/GPS Antenna Specification (1562 – 1612 MHz) – Cable 5		
VSWR	< 2.0 ± 4MHz	
Gain	26dB LNA	
Out of Band Rejection, dB	> 40dB	
Typical Noise Figure, dB	-2.7 dB	
Operating Voltage	3 – 5 VDC	
Typical Current, mA	15	
External Antenna Port for Whip Antenna – Cable 6		
Frequency Band Supported, MHz	136-174 / 340-520 / 617-960 / 1690-2700 / 2400-2500 / 4900-6000 MHz	

Every Ventev antenna is RoHS compliant and covered by company's 2-year warranty program.

Multiband 5-in-1 Sharkfin Antenna

2x 617-6000MHz, 2x 2.4/5GHz, 1x GNSS, 1x Whip/Terminal Ant

Mechanical Specifications	
Product Dims (L x W x H)	190 x 60 x 70 mm (7.5 x 2.4 x 2.8 in)
Input Connector / Pigtail	Cellular Cables (leads #1 to 2) SMA Male; 15ft Pigtail w/ RG58 Wi-Fi Cables (leads #3 to 4): RPSMA Male; 15ft Pigtail w/ RG58 GNSS/GPS Cable (lead #5): SMA Male; 15ft Pigtail w/ RG174 External Whip Antenna Cable (lead #6): SMA Male; 15ft Pigtail w/ RG58
Radome	UV Stabilized ABS. Black (White color option available with 25unit MOQ; Contact Ventev Sales)
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Ingress Protection	IP69K
Mounting	Bolt Mount through 22mm mounting hole
Application	Indoor or Outdoor
Product Weight	1.1Kg (2.4 lbs)