







Ruggedized metal enclosure with flexible, low power options

Operates across wide temperature ranges

-40°F - 149°F / -40°C - 65°C

Fanless design

Low power consumption with a USB-C power input option

Cost-effective and scalable for mass deployment

\$599*

*Pricing applies to US region only, other regions may vary.

BR2 Micro









Specifications

WAN Interface 1x 10/100/1000M Ethernet ¹

2x Embedded Cellular Modems

LAN Interface 1x 10/100/1000M Ethernet ¹

1x USB-C ²

SpeedFusion Features ² Hot Failover, Smoothing,

Bandwidth Bonding

No.of SpeedFusion VPN Peers 2 / 5 ³

Router Throughput 300Mbps

SpeedFusion VPN Throughput

- No Encryption 80Mbps - 256-bit AES 60Mbps

Recommended Users 1 - 60

Cellular Data Rate ⁴ (Downlink/Uplink) CAT-4: 150 Mbps / 50 Mbps

Antenna Connectors 4x MMCX Cellular Antenna Connectors

1x MMCX GPS Antenna Connector

Power Input AC Adapter: AC Input 100V–240V / DC Output 12V

Power Port: 10V – 30V DC USB-C Port: 9V DC

Power Consumption 8W (nominal), 13W (max.)

Dimension 2.99 x 3.25 x 1.69 inches / 76 x 83 x 43 mm

Weight 0.77 pounds / 350 grams

Operating Temperature $-40^{\circ} - 149^{\circ} \text{F} / -40^{\circ} - 65^{\circ} \text{C}$

Humidity 15% – 95% (non-condensing)

Package Content 1x BR2 Micro

1x 12V 2A 4 Pin Power Supply (ACW-632)

1x USB-C to USB-C Cable with Screw Locking (ACW-620)

1x USB-C to USB-A Adapter (ACW-622)

4x M2.5 x 3mm Screws 1 pair of Mounting Brackets

SIM Option Nano-SIM (4FF)

Peplink eSIM

BYO eSIM (2 profiles per modem) RemoteSIM from SIM Injector

FusionSIM

Warranty 1-Year Limited Warranty

Specifications are subject to change without notice.

¹ WAN port can be configured as LAN port via the Web Admin.

² The USB-C LAN interface is equipped with Ethernet to USB Adapter based on the AX88179 chipset, enabling virtual Ethernet connectivity for any device through a USB connection.

Please ensure the appropriate drivers are installed.

Requires a PrimeCare subscription, complimentary for the first year.

⁴ Theoretical maximum data rates





Ordering Information

Product Code	Regions^	LTE Bands	3G Bands
MAX-BR2-MICRO-LTE-US-PRM	North America*	B2, B4, B5, B12, B13, B14, B66, B71	B2, B5
Embedded Modem(s): 2x CAT-4	*US Carrier Certifications: AT&T, T-Mobile, Verizon, FirstNet		
MAX-BR2-MICRO-LTE-E-PRM Embedded Modem(s): 2x CAT-4	APAC, EMEA	B1, B3, B5, B7, B8, B20, B38, B40, B41	B1, B5, B8

 $^{{}^{\}wedge}$ Regions are for reference only. For specific location compatibility, please refer to the bands.

Featured Add-ons

Product Code	Description
PRM-B-1Y / PCP-B-1Y	PrimeCare B / PrimeCare+ B (1-Year)
PRM-B-2Y / PCP-B-2Y	PrimeCare B / PrimeCare+ B (2-Year)
PRM-B-4Y / PCP-B-4Y	PrimeCare B / PrimeCare+ B (4-Year)
ACW-634	10ft / 3m DC Power Cable
ACW-643	Vehicle Cigarette to Molex Power Cable
ACW-791	Peplink 4-Pin to USB-C Power Cable
BR2-MICRO-ACW-KIT	BR2 Micro Accessory Kit • 4x 3m MMCX to SMA-F Magnetic Cellular Antenna Base (ACW-414) • 1x 5m MMCX Magnetic GPS Antenna (ACW-415) • 4x Cellular Antenna (ACW-237)